



Catalog Number: Product ID: UPC Number: EAN Number: Status: **2268** 7TBD105240R0002 78621002268 05414363098379 Active

Liquidtight Strain Relief Cord Connector, 1/2 Inch, 90 Degree Bend, Meets Coast Guard CG293, Cord Range 0.250 to 0.375 Inch, Malleable Iron

Meets Coast Guard CG293

Header

3D Model

Available on Website

North American Specifications (UNSPSC)	
UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	T&B
Туре	Strain Relief Cord Connectors-90 Degree
Special Features	Meets Coast Guard CG293
Application	Suitable for Use In Hazardous Locations Where
	General Purpose Equipment is Specifically Permit-
	ted by NEC 501-4(B).
Standard	UL E13938, CSA
Size	1/2 Inch
Conductor Range	0.250 to 0.375 Inch
Material	Malleable Iron
Color	Metallic

European Specifications (ETIM)

EC000441 Cable screw gland
NPT
1/2 inch
15.875mm
6.35-9.525mm
Metal
Other
Natural colour
90°-elbow
Y

Packaging

Inner Quantity	25
Inner Dimensions (inches)	6.2x5.2x4.3
Outer Quantity	50
Outer Dimensions (inches)	11.1x6.5x5.1
Weight Uom	23 lbs. per 100

Documents / Support Tools

Technical Data Sheet US

Technical Data Sheet CA

Available on Website Available on Website

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com



Actual

Representative