

Actual



Representative

5331GR

Catalog Number: Product ID: 7TAD012420R0042 **UPC Number:** 78621089997 **EAN Number:** 05414363143123

Status: Active

3/8 Inch Steel External Bonding Liquidtight Insulated Connector

Ability to install quickly with low torque effort

| Header | |
|----------|----------------------|
| 3D Model | Available on Website |

| North American Specifications (UNSPSC) | | |
|--|--|--|
| UNSPSC | 39121420 Liquid tight connectors | |
| IGCC | 4585 Liquid tight connectors | |
| Brand Name | T&B | |
| Туре | Grounding Connectors-Straight | |
| Application | To positively bond conduit to box or enclosure | |
| Standard | UL E3060, CSA | |
| Size | 3/8 Inch | |
| Material | Steel | |
| Finish | Electro Zinc Plated/Chromate Coating | |

| European Specifications (ETIM) | | |
|---|---|--|
| · | • | |
| ETIM | EC001180 Screw connection for protective metallic | |
| | hose | |
| Nominal size in inch | 3/8 inch | |
| Model | Straight | |
| Revolving thread | N | |
| Construction type | External thread | |
| Connection type screw connection to | Thread | |
| housing | | |
| Thread type | NPT | |
| Thread connection size | Other | |
| One-piece | N | |
| Material housing | Steel | |
| Approved in combination with protective | Υ | |
| conduit CSA | | |
| Approved in combination with protective | Υ | |
| conduit I II | | |

| Packaging | |
|---------------------------|-----------------|
| Inner Quantity | 25 |
| Inner Dimensions (inches) | 6x4x4 |
| Outer Quantity | 100 |
| Outer Dimensions (inches) | 12.7x8.7x4.5 |
| Weight Uom | 16 lbs. per 100 |

| Documents / Support Tools | |
|----------------------------------|----------------------|
| Technical Data Sheet US | WSD-001319 |
| Technical Data Sheet CA | Available on Website |
| Technical Data Sheet Global | TDS000120 |
| Catalog US 1 | Available on Website |

For further technical assistance, please contact us...



Memphis, TN 38125 www.tnb.com 8155 T&B Blvd. Memphis, TN 38125 Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com