



Actual

**Catalog Number:** 15-236  
**Product ID:** 7TAA008400R0007  
**UPC Number:** 78378615236  
**EAN Number:** 05414363138143  
**Status:** Active

Wire Pulling Lubricant, Semi-Synthetic Base, Freezing Point 25 Degrees F (-4 Degrees C), High Temperature Stability, 200 Degrees F (93 Degrees C), Yellow Color, 1 Quart Squeeze Bottle

- Preferred semi-synthetic base formulation.
- Retains lubricating properties and will not separate up to 200 degree F. Will not separate after freezing.
- Superior adherence to cable.
- Recommended for use on all commonly used wire and cable including high voltage cable and all U.L. listed conduits.
- Dries to slick, waxy film.
- Non-toxic, no silicones, non-staining, easy clean up.
- Suitable for use with wire or cable insulated with rubber (R, RH, etc.), Neoprene, nylon and PVC plastics (T, TW, THW, THHN, etc.), Hypalon\*, high density polyethylene and Cross Linked Polyethylene (XLP).
- Not recommended for use on asbestos or low density polyethylene insulated cables. Compatible with semi conducting jackets present on high voltage cable.

### North American Specifications (UNSPSC)

UNSPSC	39121722 Wire and cable pulling device
IGCC	5072 Wire and cable pulling device
Brand Name	T&B
Type	Wire Installation & Wire Pulling
Special Features	Preferred semi-synthetic base formulation.
Application	Suitable for use with wire or cable insulated with rubber (R, RH, etc.), Neoprene, nylon and PVC plastics (T, TW, THW, THHN, etc.), Hypalon*, high density polyethylene and Cross Linked Polyethylene (XLP).
Standard	UL E43782

### Packaging

Outer Quantity	12
Outer Dimensions (inches)	14.5x9.7x11.4
Weight Uom	2.09 lbs. Each

### Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website
Safety Data Sheet (SDS) US	SDS-00038-TB2
Safety Data Sheet (SDS) Canada	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)