



Actual

Catalog Number: LL306
Product ID: 7TBA014460R0002
UPC Number: 78621078705
Status: Active

Aluminum Lay-in-Lug Connector, Conductor Range 6-3/0 AWG, Stud Size 0.33 Inches

- Dual-rated for both copper and aluminum conductor. Manufactured from 6061-T6 aluminum alloy for maximum strength and conductivity.
- Open-faced design enables installer to quickly lay-in grounding conductor as jumper to multiple conduits with no break in ground conductor.

North American Specifications (UNSPSC)

UNSPSC	39121613 Grounding devices or assemblies
IGCC	4909 Grounding devices or assemblies
Brand Name	Blackburn
Type	Mechanical Grounding
Special Features	Dual-rated for both copper and aluminum conductor. Manufactured from 6061-T6 aluminum alloy for maximum strength and conductivity.
Standard	UL E9809
Conductor Size	#6-3/0 AWG
Conductor Material	Aluminum
Insulation	No

Packaging

Inner Quantity	10
Inner Dimensions (inches)	4x4x3
Outer Quantity	50
Outer Dimensions (inches)	21.5x4.75x4
Weight Uom	19 lbs. per 100

Documents / Support Tools

Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com