

Product availability : Non-Stock - Not normally stocked in distribution facility

Price\* : 81.00 USD



### Main

Range	TeSys
Device short name	GV3B
Product or component type	Undervoltage trip
Device application	Control

### Complementary

Product compatibility	GV3ME
[Uc] control circuit voltage	220 V AC 50 Hz 240 V AC 50 Hz 277 V AC 60 Hz
Control circuit voltage limits	0.8...1.1 Un
[Ui] rated insulation voltage	600 V AC CSA C22.2 No 14 600 V AC UL 508 690 V AC IEC 60947-1
Threshold tripping voltage	0.7...0.35 Un
Inrush power in VA	12 VA AC
Inrush power in W	7 W DC
Hold-in power consumption in VA	7 VA AC
Hold-in power consumption in W	2.5 W DC
Operating time	10 ms IEC 60947-1
On-load factor	100 %
Connections - terminals	Screw clamp terminals 1 0...0 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> ) flexible without Screw clamp terminals 1 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) solid Screw clamp terminals 2 0...0 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> ) flexible without Screw clamp terminals 2 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) solid Screw clamp terminals 1 0...0 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> ) flexible with Screw clamp terminals 2 0...0 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> ) flexible with
Tightening torque	1.2 N.m screw clamp terminals
Mechanical durability	15000 cycles
Quantity per set	Set of 10
Product weight	0.15 lb(US) (0.07 kg)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	22366 - MAN STR PROTECTORS-GV1/GV3
Discount Schedule	I11
GTIN	00785901258100
Nbr. of units in pkg.	1
Package weight(Lbs)	0.16
Returnability	N
Country of origin	FR

Contractual warranty

Warranty period	18 months
-----------------	-----------