

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [19403-1230](#)  
**Status:** **Active**  
**Overview:** Self-Contained Power Connector (SCPC)  
**Description:** Self-Contained Power Connector, Panel Mount Housing, 10 AWG

**Documents:**

[Drawing \(PDF\)](#) [Product Literature \(PDF\)](#)  
[RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**

CSA LR18689  
 UL E152602

**General**

Product Family I/O Connectors  
 Series [19403](#)  
 Application Wire-to-Wire  
 Component Type Plug, Receptacle  
 Overview Self-Contained Power Connector (SCPC)  
 Product Literature Order No 987650-0531  
 Product Name SCPC  
 Type N/A  
 UPC 800755234534

**Physical**

Circuits (Loaded) 2  
 Circuits (maximum) 2  
 Circuits Detail 2 Circuits with Ground  
 Durability (mating cycles max) 250  
 Flammability 94-5VA  
 Lock to Mating Part Yes  
 Material - Plating Mating Tin  
 Net Weight 21.082/g  
 Number of Rows 1  
 Orientation Vertical  
 Packaging Type Bag  
 Panel Mount Yes  
 Pitch - Mating Interface 10.10mm  
 Polarized to Mating Part Yes  
 Surface Mount Compatible (SMC) N/A  
 Temperature Range - Operating -35°C to +85°C  
 Termination Interface: Style N/A  
 Wire Size AWG 10


**Electrical**

Current - Maximum per Contact 20A  
 Voltage - Maximum 300V

**Material Info**

**Reference - Drawing Numbers**

Sales Drawing SD-19403-128



Series

*image - Reference only*

**EU RoHS**

**ELV and RoHS  
Compliant**

**REACH SVHC**

Not Reviewed

**Low-Halogen Status**

**Not Reviewed**

**China RoHS**



**Need more information on product  
environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

[19403Series](#)

**Mates With**

[19403-1300](#) Self-Contained Power Connector for Solid or Stranded Nonmetallic Sheathed Cable, 10 AWG

**Use With**

[19403-1240](#) Strip Carried Terminal,  
[19403-1241](#) Loose Piece Terminal