Catalog Number:
 GRUPE-062-9-C

 Product ID:
 7TAG009750R0047

 UPC Number:
 72849410526

 EAN Number:
 05414363023814

Status: Active

Extruded Grommeting, Natural Un-Cut Polyethylene for Temperatures up to 85 Degrees Celsius (185 F), Height of 5.08mm (0.20 Inches), Width of 4.32mm (0.17 Inches), Thickness 1.14mm (0.045 Inches), Width Maximum Panel Thickness of 1.57mm (0.062 Inches), 30.48m (100 Foot) Reel

- Used to line panel edges and knockouts where the chafing of wires is a concern.
- Available in 8 stock sizes in 100-ft. lengths for panels from .040 .250 inches thick and in a variety of stocked materials to cover a wide range of applications.
- Application Tools: SR-100

North American Specifications (UNSPSC)		
UNSPSC	39131603 Grommet edging	
IGCC	5393 Grommet edging	
Brand Name	Catamount	
Туре	Grommeting	
Special Features	Used to line panel edges and knockouts where the chafing of wires is a concern.	
Color	Natural	
Panel Thickness	0.062	
Material	Un-Cut Polyethylene	

European Specifications (ETIM)		
ETIM	EC002604 Cable bundle hose	
Material	Plastic	
Material quality	Polyethylene	
Colour	Natural colour	
Transparent	N	

Packaging	
Inner Quantity	1
Inner Dimensions (inches)	15x12x1.25
Outer Quantity	15
Outer Dimensions (inches)	18x12.5x12
Weight Uom	1.12 lbs. Each

Documents / Support Tools

Technical Data Sheet CA Available on Website

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Actual

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com