

Catalog Number: 283-I-TB

 Product ID:
 7TAA106070R0037

 UPC Number:
 78620989568

 EAN Number:
 05414363450368

Status: Active

Squeeze Connector, 90 Degree Bend, Trade Size 3 Inch, Knockout Size 3 Inch, Cable Range 3.100 to 3.640 Inch, Insulated Throat, Malleable Iron

North American Specifications (UNSPSC)	
UNSPSC	39121419 Flex connectors
IGCC	4573 Flex connectors
Brand Name	T&B
Туре	Armored Cable/Flexible Metal Conduit Fittings
Special Features	Cap Lifts off by Simply Loosening Screws Part
	Way, Only Two Screws to Tighten
Application	For Use with Armored Cable and Flexible Metal
	Conduit
Standard	UL E23018, CSA 2884, cULus
Size	3 Inch
Connection	90 Degree
Conductor Range	3.100 to 3.640 Inch
Material	Malleable Iron
Finish	Zinc Plated
Color	Metallic
Insulation	Insulated Throat

European Specifications (ETIM)	
ETIM	EC001180 Screw connection for protective metallic
	hose
Nominal size in inch	3 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to	Other
housing	
Material housing	Other
Approved in combination with protective	Υ
conduit CSA	
Approved in combination with protective conduit UL	Υ

Packaging	
Outer Quantity	1
Outer Dimensions (inches)	11.5x10.5x6.25
Weight Uom	5.99 lbs. Each

Documents / Support Tools

Technical Data Sheet Global WSD-000349

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com