



Actual



Representative

Catalog Number: 5223
Product ID: 7TAD013160R0010
UPC Number: 78621005223
EAN Number: 05414363142676
Status: Active

3/4 Inch Insulated Compression Connector, Steel Electro Zinc Plated, Insulator Thermoplastic for Use with EMT Conduit

- Rings designed to positively bond conduit to fitting; unique locknut design provides effective bond between fitting and box or enclosure; ground continuity is assured.
- Nylon insulator firmly secured in place-protects conductors, reduces wire pulling effort and prevents thread damage in handling.
- To provide a connection between tubing and the connector, and to couple ends of tubing.

Header

3D Model Available on Website

North American Specifications (UNSPSC)

UNSPSC	39121434 Electrical metallic tubing EMT connectors
IGCC	4611 Electrical metallic tubing EMT connectors
Brand Name	T&B
Type	EMT Conduit Fittings
Special Features	Rugged All Steel Construction
Application	To Connect and Effectively Bond Electrical Metallic Tubing to a Box or an Enclosure
Standard	UL E16592, CSA
Size	3/4 Inch
Material	Steel
Finish	Electro Zinc Plated

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	3/4 inch
Model	Straight
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	NPT
One-piece	N
Material housing	Steel
Surface protection	Other

Packaging

Inner Quantity	50
Inner Dimensions (inches)	4x4.5x6
Outer Quantity	250
Outer Dimensions (inches)	21.4x9.5x6.3
Weight Uom	13.5 lbs. per 100

Documents / Support Tools

Technical Data Sheet CA	Available on Website
Technical Data Sheet Global	wsd-000051

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com