Product data sheet Characteristics

9001K2L38R20 PUSHBUTTON OPERATOR 30MM TYPE K +OPTIONS



Price*: 125.00 USD

9001K2L38R20 has not been replaced. Please contact your customer care center for more information.



Main

		•
Range of product	Harmony 9001K	,
Product or component type	Complete illuminated push-button	
Device short name	9001K	g
Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Operator additional information	Screw-on plastic mushroom	
Light source	Incandescent	

Complementary

Shape of signaling unit head	Round	
Type of operator	Spring return	
Operator profile	Mushroom Ø 35 mm red unmarked	989
Bulb base	BA 9s	<u> </u>
Light block supply	Direct	to
Mechanical durability	5000000 cycles	<u> </u>
Operating position	Any position	- in
Product weight	0.37 lb(US) (0.166 kg)	Stiff

Environment

		τ
Standards	EN/IEC 60947-1	
	EN/IEC 60947-5-1	
	EN/IEC 60947-5-4	2.
	JIS C 4520	2.
	JIS C 852	
	UL 508	
	CSA C22.2 No 14	5
Product certifications	NEMA	
	UL 508	,
Protective treatment	TC	
		<u> </u>

Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
Vibration resistance	7 gn (f = 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn conforming to IEC 60068-2-27
Electrical shock protection class	Class II conforming to IEC 61140
IP degree of protection	IP66 conforming to IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4

Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	00785901180098
Nbr. of units in pkg.	1
Package weight(Lbs)	0.5
Returnability	N
Country of origin	MX

Contractual warranty