Catalog Number:
 GRFR-085-WH-C

 Product ID:
 7TAG009750R0013

 UPC Number:
 72849409357

 EAN Number:
 05414363023425

Status: Active

Extruded Grommeting, Flame Retardant White Polyethylene, Height of 5.08mm (0.20 Inches), Width of 4.32mm (0.17 Inches), Thickness 1.32mm (0.05 Inches), Maximum Panel Thickness of 2.16mm (0.085 Inches), 30.48m (100 Foot) Reel

- Used to line panel edges and knockouts where the chafing of wires is a concern.
- Available in 8 stock sizes in 100-ft. lengths for panels from .040 .250 inches thick and in a variety of stocked materials to cover a wide range of applications.
- Application Tools: SR-100

North American Specifications (UNSPSC)

UNSPSC 39131603 Grommet edging

IGCC 5393 Grommet edging

Brand Name Catamount

Type Grommeting

Special Features Used to line panel edges and knockouts where the chafing of wires is a concern.

Color White

Panel Thickness 0.085

Material Flame Retardant Polyethylene

European Specifications (ETIM)

ETIM EC002604 Cable bundle hose

Material Plastic

Material quality Polyethylene

Colour White

Packaging		
Outer Quantity	15	
Outer Dimensions (inches)	18.25x12.75x13.5	
Weight Uom	1.65 lbs. Each	

Documents / Support Tools

Technical Data Sheet CA Available on Website

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Actual

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com