

# T&B® Electricians' Supplies

## Wire Connectors and Termination Products



### Marrette® Black™ High Temperature Wire Connectors

The Marrette® Black™ connector's high temperature rating makes it the best solution for high wattage lighting fixtures and signs.

#### External Cap

- Made of rugged, phenolic material and 150°C-rated.
- Large, finely ribbed, "barrel-shaped" cap – makes it easier to grip even when hands are greasy or damp.
- Deep, wide throat ensures full insulation coverage.
- Threaded entry helps guide large wire bundles right into the spring.

#### Inner spring

- Internal round spring design multiplies the "twist-on" torque applied by the leverage and wedge

action, to firmly crush wires into a solid joint.

- Model #37 Black™ – uses a square wire expansion spring for additional gripping power on large conductor combinations.
- Unique copper-coated spring helps resist corrosion.
- CSA (LR6591), UL (424H)
  - Model nos. 29 & 30 Black™ are approved for circuit and fixture type connections up to 300V only.
  - Model nos. 31, 33, 35 & 37 Black™ are approved for circuits up to 600V, and lighting fixtures and signs up to 1,000V.
- Convenient packaging - sized right and job-site ready!

### Marrette Black High Temperature Wire Connectors

Cat No.	Description	Wire Range*	Model	Std. Ctn.
<b>29P</b>	Black	#22-16	29	1000
<b>29BP</b>	Black	#22-16	29	1000
<b>29BK</b>	Black	#22-16	29	10000
<b>30P</b>	Black	#22-14	30	1000
<b>30BP</b>	Black	#22-14	30	1000
<b>30BK</b>	Black	#22-14	30	10000
<b>31P</b>	Black	#18-14	31	1000
<b>31KP</b>	Black	#18-14	31	5000
<b>31BP</b>	Black	#18-14	31	1000
<b>31BK</b>	Black	#18-14	31	10000
<b>33P</b>	Black	#18-12	33	1000
<b>33KP</b>	Black	#18-12	33	5000
<b>33BP</b>	Black	#18-12	33	10000
<b>33BK</b>	Black	#18-12	33	10000
<b>35P</b>	Black	#18-10	35	1000
<b>35KP</b>	Black	#18-10	35	2500
<b>35BP</b>	Black	#18-10	35	1000
<b>35BK</b>	Black	#18-10	35	5000
<b>37P</b>	Black	#16-8	37	500
<b>37BP</b>	Black	#16-8	37	500