



Representative

Catalog Number: 2828
Product ID: 7TAD105140R0023
UPC Number: 78621002828
Status: Active

UF Cable Fitting, 3/4 Inch, Cable Range Maximum .675 x .280, Minimum .525 x .19 Inch, Nylon, Black

- Tapered threaded hub, liquidtight and dust tight; hand tightens-no tools required. Corrosive and weather resistant nylon for outdoor and indoor applications.

Header

3D Model Available on Website

North American Specifications (UNSPSC)

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	T&B
Type	UF Cable Fittings
Special Features	Tapered Threaded Hub, Liquidtight and Dust Tight; Hand Tightens-No Tools Required. Corrosive and Weather Resistant Nylon.
Application	Indoor and Outdoor Use
Standard	UL E17583, CSA, RoHS
Size	3/4 Inch
Conductor Range	0.525x0.190 to 0.675 to 0.280 Inch
Material	Nylon
Color	Black

European Specifications (ETIM)

ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	3/4 inch
Thread length	15.75mm
Material	Plastic
Material quality	Polyamide (PA)
Colour	Black
Model	Straight

Packaging

Inner Quantity	10
Inner Dimensions (inches)	6x4.5x3
Outer Quantity	100
Outer Dimensions (inches)	13x11x9
Weight Uom	8.88 lbs. per 100

Documents / Support Tools

Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website
Instruction Sheet 1	TA02460-TB2

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com