

Catalog Number: 282-I-TB
Product ID: 7TAA106070R0035
UPC Number: 78620989564
EAN Number: 05414363450214
Status: Active

Squeeze Connector, 90 Degree Bend, Trade Size 2-1/2 Inch, Knockout Size 2-1/2 Inch, Cable Range 2.520 to 3.100 Inch, Insulated Throat, Malleable Iron

North American Specifications (UNSPSC)

UNSPSC	39121419 Flex connectors
IGCC	4573 Flex connectors
Brand Name	T&B
Type	Armored Cable/Flexible Metal Conduit Fittings
Special Features	Cap Lifts off by Simply Loosening Screws Part Way, Only Two Screws to Tighten
Application	For Use with Armored Cable and Flexible Metal Conduit
Standard	UL E23018, CSA 2884, cULus
Size	2-1/2 Inch
Connection	90 Degree
Conductor Range	2.520 to 3.100 Inch
Material	Malleable Iron
Finish	Zinc Plated
Color	Metallic
Insulation	Insulated Throat

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	2 1/2 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Other
Material housing	Other
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UL	Y

Packaging

Outer Quantity	1
Outer Dimensions (inches)	12.5x6.3x6.5
Weight Uom	4.09 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000349
--------------------------------	------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com