

Product data sheet

Characteristics

8501CO6V04

Power Relay - 277VAC Coil - SPST - 1NO-0NC - 2.0 HP - 30A Resistive at 300V

Product availability : Stock - Normally stocked in distribution facility



Price* : 32.70 USD



Main

Range of product	Power Relay 8501C
Product or component type	Power relay
Device short name	Type C
Line Rated Current	30 A
Device application	Suited for controlling small single phase motors and other light loads
Switch function	SPST
Contacts type and composition	1 NO
[Uc] control circuit voltage	277 V AC 60 Hz
Rated power in hp	2 hp
Maximum switching voltage	600 V AC

Complementary

Catalog class	8501
Phase	1 phase
Connections - terminals	Screw clamp terminal
AWG gauge	AWG 10 copper
Tightening torque	11...15 lbf.in
Hold-in power consumption in VA	10 VA
Mounting support	Panel mounting

Environment

Ambient air temperature for operation	-22...122 °F
Product certifications	UL listed file E78351 CCN NLDX CSA
Height	2.43 in
Width	2.5 in

Depth	2.25 in
-------	---------

Ordering and shipping details

Category	21131 - 8501 C
Discount Schedule	CP2
GTIN	00785901059554
Nbr. of units in pkg.	1
Package weight(Lbs)	0.52000000000000002
Returnability	Y
Country of origin	CN

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1014 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------