Product data sheet Characteristics


XCRZ12

contact block XCRZ - 2X(1NO+NC) - snap action

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 166.00 USD



Main

Range of product	OsiSense XC	<u> </u>
Series name	Special format	5
Product or component type	Limit switch contact block with mounting plate	
Device short name	XCRZ	
Product compatibility	XCRA XCRB XCRE XCRF	iith
Electrical connection	Screw-clamp terminals, 1 x 0.342 x 1.5 mm ²	
Number of poles	4	
Contacts type and composition	2 x (1 NC + 1 NO)	
Contact operation	Snap action	9
Contacts material	Silver plated contacts	9
Positive opening	With	-

Complementary

Contacts insulation form	Zb	. 2
Minimum actuation speed	0.01 mm/s	
Contact code designation	A300; AC-15(Ue = 240 V, Ie = 3 A) EN/IEC 60947-5-1 appendix A Q300; DC-13(Ue = 250 V, Ie = 0.27 A) EN/IEC 60947-5-1 appendix A	
Resistance across terminals	< 25 mOhm IEC 60255-7 category 3	
[Ui] rated insulation voltage	300 V CSA C22.2 No 14 300 V UL 508 500 V 3 IEC 60947-1 500 V NF C 20-040 group C 500 V VDE 0110	mantation is not in
[Uimp] rated impulse withstand voltage	6 kV IEC 60664 6 kV IEC 60947-1	
Short-circuit protection	10 A cartridge fuse gG	

Electrical durability	5000000 cycles DC-13, 120 V 4 W, < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1
	5000000 cycles DC-13, 24 V 10 W, < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
	5000000 cycles DC-13, 48 V 7 W, < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C

Ordering and shipping details

Category	22449 - LIMIT SWITCHES,ACCESSORIES
Discount Schedule	Т
GTIN	003389110652482
Nbr. of units in pkg.	1
Package weight(Lbs)	0.35999999999999
Returnability	N
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1010 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Contractada Warranty		
Warranty period	18 months	