

# Product data sheet

## Characteristics

# XZCPV0941L5

pre-wired connectors XZ - straight female - M8 - 4 pins - cable PVC 5m

Product availability : Stock - Normally stocked in distribution facility

Price\* : 19.00 USD



### Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

### Complementary

Electrical connection	M8, 4 pins straight female connector
Cable connector fixing	Screw-on
Collar material	Metal
Status LED	Without
Cable length	16.4 ft (5 m)
Cable outer diameter	0.18 in (4.6 mm)
Cable composition	4 x 0.25 mm <sup>2</sup>
Wire insulation material	PVC
System Voltage	60 V AC 75 V DC
Line Rated Current	3 A
Contact resistance	5000 μOhm
Insulating resistance	1 GΩ
Product weight	0.44 lb(US) (0.2 kg)

### Environment


IP degree of protection	IP65 IP67
Product certifications	CULus
Ambient air temperature for operation	-13...176 °F (-25...80 °C) (static)
Ambient air temperature for storage	-13...176 °F (-25...80 °C)

### Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3

GTIN	00785901414919
Nbr. of units in pkg.	1
Package weight(Lbs)	0.390000000000000001
Returnability	Y
Country of origin	CZ

**Offer Sustainability**

RoHS (date code: YYWW)	Compliant - since 1201 - Schneider Electric declaration of conformity <a href="#"> Schneider Electric declaration of conformity</a>
------------------------	---

**Contractual warranty**

Warranty period	18 months
-----------------	-----------