
MAXI® Circuit Breakers

Series 190

Auto, Manual & Modified Reset Circuit Protectors



Series 190 MAXI® Auto, Manual & Modified Reset Circuit Protectors

SPECIFICATIONS

Single Pole Thermal Type Breakers

Ratings: 8A to 50A; Series 191 & 192 12 VDC; Series 193, 194 & 195 24 VDC.


Operating Temperature: -20°F (-10°C) to 150°F (65°C). Storage Temperature: -20°F (-10°C) to 200°F (93°C). Applications: Trucks, RV's, buses, boats, portable gener-

ators, welding equipment, etc.


Interchangeable Blade Terminals: with MAXI® blade fuse.

Approvals: Complies with SAE standard J553.

Dimensions





Terminal Options



PART NUMBERING SYSTEM

Series	Rating	Terminal	Cover	Button	Marking
19			□ –		
191 – Auto Reset 192 – Modified Reset 193 – Manual Reset 194 – Auto Reset	08 – 8 amps 10 – 10 amps 15 – 15 amps 20 – 20 amps	01 – MAXI 05 – .250 Q.C.	M – Metal* P – Plastic	Blank – No button 1 – Black 2 – White	Consult factory for special markings.
195 – Modified Reset	25 – 25 amps 30 – 30 amps 35 – 35 amps** 40 – 40 amps** 50 – 50 amps**	 Metal cover aids heat dissipation. Mandatory for Modified Resets. Recommended, but not mandatory on Auto Resets. ** Only available on 01 Terminal. 			





The only controlled copy of this BIF document is the electronic read-only version located on the Bussmann Network Drive. All other copies of this BIF document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.