Thomas&Betts



Actual



Representative

Catalog Number: Product ID: **UPC Number:** EAN Number: Status:

2922 7TBD105170R0002 78621002922 05414363101741 Active

Liquidtight Strain Relief Connector, 1/2 Inch, Straight, Cord Range 0.500 to 0.750 Inch, Throat Diameter 9/16 Inch, Steel Body, Glandnut, and Grip, Rubber Bushing

- · Reduced overall size, fits into tighter spaces.
- Gland nut designed to restrict cable bending.
- · Suitable for Ordinary, Wet or Dry locations.

· Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

North American Specifications (UNSPSC)	
UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	T&B
Туре	Cord Connectors-Straight
Special Features	Extended Range with Superior Strain Relief
Application	Provide a Means for Passing a Cord Cable Into an
	Enclosure Through a Bulkhead
Standard	UL E13938, CSA 52391
Size	1/2 Inch
Conductor Range	0.500 to 0.750 Inch
Material	Steel
Color	Metallic
Environmental Conditions	Ordinary, Wet, or Dry Locations

European Specifications (ETIM)

• • •	,
ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	1/2 inch
Thread length	15.875mm
Suitable for cable diameter	12.7-19.05mm
Material	Metal
Material quality	Steel
Colour	Natural colour
Model	Straight
Strain relief	Υ
Packaging	
Inner Quantity	10
Inner Dimensions (inches)	4x4x3
Outer Quantity	100

inner Dimensions (inches)	4X4X3
Outer Quantity	100
Outer Dimensions (inches)	21.5x8.8x4
Weight Uom	17.5 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet US Technical Drawing / Data Sheet Canada Available on Website

Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125

T&B Technical Support MS 3B-50 8155 T&B Blvd.

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289



www.tnb.com

Memphis, TN 38125

Fax: (901) 252-1321 Email:techsupport@tnb.com