Product data sheet Characteristics

9001BG209

control station type B - 2 operators - Raise-Lower - NEMA 1

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 107.00 USD



Main

Range of product	Harmony 9001B
Product or component type	Complete control station
Device short name	9001BG
Control station application	Two functions
Colour of base of enclosure	Grey

Complementary

0		
A - ti-		
Main Range of product	Harmony 9001B	
Product or component type	Complete control station	
Device short name	9001BG	
Control station application	Two functions	
Colour of base of enclosure	Grey	
Complementary		
Material	Cast zinc	
Marking	CE	
Type of operator	Momentary	
Control station composition	2 push-buttons (RAISE-LOWER marking) white	
Contacts type and composition	2 NO	
Mechanical durability	5000000 cycles	
Connections - terminals	Screw-clamp terminal	
[le] rated operational current	5 A at 600 V - utilisation category AC	
Device mounting	Surface	
Type of installation	Indoor	
Environment		
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
NEMA degree of protection	NEMA 1	
Product certifications	CSA LR25490 class 3211 03	
Froduct certifications	UL listed file E42259 CCN NKCR	
lun 24, 2049		

Environment

Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
NEMA degree of protection	NEMA 1
Product certifications	CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR

Ordering and shipping details

Category	21421 - 9001 B (NOT BW70 - BW80)
Discount Schedule	CS1
GTIN	00785901857372
Nbr. of units in pkg.	1
Package weight(Lbs)	1
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1308 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months	