

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
	V	REV; ECO-14-002626	18MAR2014	GG	PJ

FINISHED WIRE DATA		
CONDUCTORS	WIRE AWG	23 AWG
	MATERIAL	SOLID BARE COPPER
INSULATION	MATERIAL	FLUOROPOLYMER
JACKET	MATERIAL	FR PVC
FILLER	MATERIAL	FLUOROPOLYMER

COLOR CODE

PAIR	
1	WHT-BLU/BLU
2	WHT-ORG/ORG
3	WHT-GRN/GRN
4	WHT-BRN/BRN

1. SEQUENTIAL FOOTAGE RETURNED TO ZERO FOR EACH LENGTH ON PUTUP LENGTHS 3000FT OR LESS.
2. INSULATION COLORS SHALL BE BLUE, ORANGE, GREEN, BROWN AND WHITE. THE INSULATION COLOR MAY BE TRANSLUCENT.
3. XX=JACKET COLOR- BL=BLUE, WT= WHITE, GY= GRAY, GN= GREEN, YL= YELLOW, OR= ORANGE, RD= RED, VT= VIOLET, BK= BLACK.
4. PRINT COLOR SHALL BE DARK BLUE, EXCEPT WHITE ON BLACK JACKET.
5. DATE CODE
6. GOVERNING SPECIFICATIONS - LATEST REVISIONS
 NEC 800
 UL 444 - CMP
 TIA-568-C.2 CAT 6A
7. REPLACE "02" FOR THE FOLLOWING FOOTAGES:
 04= 2000', 05= 2500', CALL FOR ADDITIONAL OPTIONS.

LEGEND TO BE REPEATED EVERY 24"

TE CONNECTIVITY 640 SERIES 4/23 AWG T256 F/UTP CMP CKULJUS CAT 6A PAT 6153826, 6150612, 6743983 XXXX FT

1 5 3 7

CATALOG NUMBER	WEIGHT		PACKAGING
	LBS/KFT	KG/KM	
TE640PF-XX02	52	77	1000' REEL

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L. HALL 11JUN03	TE TE Connectivity	
DIMENSIONS: INCHES		CHK R. SPEER 13JUN03		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD R. SPEER 13JUN03	NAME CABLE, CATEGORY 6A, XG SYSTEM, 4 FTP, CMP	
0 PLC ± -		PRODUCT SPEC	-	
1 PLC ± .1		APPLICATION SPEC	-	
2 PLC ± .02		WEIGHT	-	
3 PLC ± .005		SIZE	A2	
4 PLC ± .0005		CAGE CODE	00779	
ANGLES ± -		DRAWING NO	C=1499416	
FINISH		RESTRICTED TO	-	
MATERIAL		CUSTOMER DRAWING	SCALE	NTS
		SHEET	1 of 1	
		REV	V	

1471-9 (3/11)

1499416