Product data sheet Characteristics

KAXZ1S142

operating head with bezel \varnothing 28.5 mm, metal - key Ronis 421



-1	W	71	9	r
	v	1	а	н

Harmony Series K	
Cam switch operating head	
KAX	
Front mounting bodies 12 and 20 A by Ø 22 mm hole	
With bezel Ø 28.5 mm, metal	
Key Ronis 421	<u> </u>
Without	
With mat black legend	
45 °	> ±
	Cam switch operating head KAX Front mounting bodies 12 and 20 A by Ø 22 mm hole With bezel Ø 28.5 mm, metal Key Ronis 421 Without With mat black legend

Complementary

		<u> </u>
Mechanical durability	1000000 cycles	
Mechanical durability	1000000 Cycles	
Product weight	0.065 kg	
i roduct weight	0.005 kg	

Environment

Protective treatment	TC	
Ambient air temperature for operation	-2555 °C	3
Ambient air temperature for storage	-4070 °C	2 2
Shock resistance	30 gn conforming to IEC 68-2-27	7
Vibration resistance	5 gn, 10150 Hz conforming to IEC 68-2-6	<u>.</u> 2
IP degree of protection	IP65 conforming to IEC 529 IP65 conforming to NF C 20-010	

Contractual warranty


•	
Warranty period	18 months

Product data sheet KAXZ1S142

Dimensions Drawings

Operating Head

For Ø 22 mm/0.87 in. Hole, Front Mounting Body



Product data sheet Mounting and Clearance

KAXZ1S142

Operating Head

Panel Cut-out

mm in

