



Actual

**Catalog Number:** GRFR-062-WH-C  
**Product ID:** 7TAG009750R0012  
**UPC Number:** 72849411481  
**EAN Number:** 05414363023418  
**Status:** Active

Extruded Grommeting, Flame Retardant White Polyethylene, Height of 5.08mm (0.20 Inches), Width of 4.32mm (0.17 Inches), Thickness 1.32mm (0.05 Inches), Maximum Panel Thickness of 1.57mm (0.06 Inches), 30.48m (100 Foot) Reel

- Used to line panel edges and knockouts where the chafing of wires is a concern.
- Available in 8 stock sizes in 100-ft. lengths for panels from .040 - .250 inches thick and in a variety of stocked materials to cover a wide range of applications.
- Application Tools: SR-100

### North American Specifications (UNSPSC)

UNSPSC	39131603 Grommet edging
IGCC	5393 Grommet edging
Brand Name	Catamount
Type	Grommeting
Special Features	Used to line panel edges and knockouts where the chafing of wires is a concern.
Color	White
Panel Thickness	0.062
Material	Flame Retardant Polyethylene

### European Specifications (ETIM)

ETIM	EC002604 Cable bundle hose
Material	Plastic
Material quality	Polyethylene
Colour	White

### Packaging

Inner Quantity	1
Outer Quantity	15
Weight Uom	23 lbs. per 100

### Documents / Support Tools

Technical Data Sheet CA	Available on Website
-------------------------	----------------------

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com