

Product data sheet

Characteristics

XZCP0266L10

pre-wired connectors XZ - elbowed female - Ø 8 mm - 3 pins - cable PUR 10m

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 33.10 USD



Main

| | |
|------------------------------------|----------------------|
| Accessory / separate part category | Cabling accessory |
| Accessory / separate part type | Pre-wired connectors |
| Series name | General purpose |

Complementary

| | |
|--------------------------|-----------------------------------------|
| Electrical connection | Ø 8 mm, 3 pins elbowed female connector |
| Cable connector fixing | Clip-on |
| Status LED | Without |
| Cable length | 32.81 ft (10 m) |
| Cable outer diameter | 0.2 in (5.2 mm) |
| Cable composition | 3 x 0.34 mm ² |
| Wire insulation material | PUR |
| System Voltage | 60 V AC 75 V DC |
| Line Rated Current | 4 A |
| Contact resistance | 5000 µOhm |
| Insulating resistance | 1 GΩ |
| Product weight | 0.47 lb(US) (0.215 kg) |

Environment

| | |
|---------------------------------------|---------------------------------------------------------------------------|
| IP degree of protection | IP65 IP67 |
| Product certifications | CULus |
| Ambient air temperature for operation | -40...176 °F (-40...80 °C) (static) 23...176 °F (-5...80 °C) (flexing) |
| Ambient air temperature for storage | -40...176 °F (-40...80 °C) |

Ordering and shipping details

| | |
|-----------------------|------------------------|
| Category | 22483 - MACHINE CABLES |
| Discount Schedule | DS3 |
| GTIN | 003389110763003 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.530000000000000003 |
| Returnability | N |
| Country of origin | CZ |

Offer Sustainability

| | |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0649 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Available |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|