

Representative

Catalog Number: 3141

 Product ID:
 7TAA106020R0011

 UPC Number:
 78621003141

Status: Active

Metal-Clad and Armored Cable Fitting, 90 Degree Bend, Trade Size 2-1/2 Inch, Knockout Size 2-1/2 Inch, Cable Range 2.812 to 3.062 Inch, Malleable Iron with Zinc Plating, Nylon Insulated

- All the advantages of the straight connector with only one screw to tighten, except in the larger sizes where there are two.
- A peep hole on top provides for easy inspection of the ABC bushing.
- Narrow design makes it easy to install connectors in adjacent knockouts.
- To connect and effectively bond armored cable or flexible metal conduit to a box or an enclosure.

Header	
3D Model	Available on Website

North American Specifications (UNSPSC)		
UNSPSC	39121419 Flex connectors	
IGCC	4573 Flex connectors	
Brand Name	T&B	
Туре	Armored Cable/Flexible Metal Conduit Fittings	
Special Features	By Far The Easiest and Best to Install When Mak-	
	ing Sharp Bends At The Enclosure or Equipments	
Application	For Use with Armored Cable and Flexible Metal	
	Conduit	
Standard	UL E23018, CSA	
Size	2 1/2 Inch	
Connection	90 Degree	
Conductor Range	2.812 to 3.062 Inch	
Material	Malleable Iron	
Finish	Electro Zinc Plated	
Color	Metallic	
Insulation	Nylon	

European Specifications (ETIM)		
ETIM	EC001180 Screw connection for protective metallic	
	hose	
Nominal size in inch	2 1/2 inch	
Model	90°-elbow	
Revolving thread	N	
Construction type	External thread	
Connection type screw connection to	Other	
housing		
Material housing	Other	
Surface protection	Zinc coated	
Thread length	25.4mm	

Packaging	
Outer Quantity	1
Outer Dimensions (inches)	8.8x5.9x6.7
Weight Uom	691.5 lbs. per 100

Documents / Support Tools	
Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website



For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com