



Actual



Representative

Catalog Number: 2641
Product ID: 7TAD105160R0003
UPC Number: 78621002641
EAN Number: 05414363190578
Status: Active

Chase Liquidtight Steel Cord Connector, Straight, 3/4 Inch, Cord Range 0.625 to 0.750 Inch

- Suitable for use in hazardous locations in Class I, Div. 2; Class II, Div 1 & 2; Class III, Div 1 & 2, where general purpose equipment is specifically permitted by NEC 500-2(a)
- Meets Coast Guard CG293

Header

3D Model Available on Website

North American Specifications (UNSPSC)

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	T&B Industrial Fitting
Type	Flexible Cord and Cable Fittings
Special Features	CSA Certified Watertight. UL Listed As Liquidtight Strain Relief, and Outlet Bushing.
Application	For Installation Where Space is Limited Inside the Enclosure
Standard	CSA, UL E13938
Size	3/4 Inch
Material	Steel

European Specifications (ETIM)

ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	3/4 inch
Suitable for cable diameter	15.875-19.05mm
Material	Other
Material quality	Steel
Colour	Natural colour
Model	Straight

Packaging

Inner Quantity	25
Inner Dimensions (inches)	6x5x4
Outer Quantity	50
Outer Dimensions (inches)	11x5.2x8.8
Weight Uom	32 lbs. per 100

Documents / Support Tools

Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com