



Actual

Catalog Number: GRUPE-125-9-C
Product ID: 7TAG009750R0050
UPC Number: 72849411244
EAN Number: 05414363023845
Status: Active

Extruded Grommeting, Natural Un-Cut Polyethylene for Temperatures up to 85 Degrees Celsius (185 F), Height of 5.58mm (0.220 Inches), Width of 5.21mm (0.205 Inches), Thickness 1.27mm (0.05 Inches), Width Maximum Panel Thickness of 3.17mm (0.125 Inches), 30.48m (100 Foot) Reel

- Used to line panel edges and knockouts where the chafing of wires is a concern.
- Available in 8 stock sizes in 100-ft. lengths for panels from .040 - .250 inches thick and in a variety of stocked materials to cover a wide range of applications.
- Application Tools: SR-100

North American Specifications (UNSPSC)

| | |
|------------------|---|
| UNSPSC | 39131603 Grommet edging |
| IGCC | 5393 Grommet edging |
| Brand Name | Catamount |
| Type | Grommeting |
| Special Features | Used to line panel edges and knockouts where the chafing of wires is a concern. |
| Color | Natural |
| Panel Thickness | 0.125 |
| Material | Un-Cut Polyethylene |

European Specifications (ETIM)

| | |
|------------------|----------------------------|
| ETIM | EC002604 Cable bundle hose |
| Material | Plastic |
| Material quality | Polyethylene |
| Colour | Natural colour |
| Transparent | N |

Packaging

| | |
|---------------------------|----------------|
| Inner Quantity | 1 |
| Inner Dimensions (inches) | 17x12x1.5 |
| Outer Quantity | 10 |
| Outer Dimensions (inches) | 18x12.5x12 |
| Weight Uom | 1.35 lbs. Each |

Documents / Support Tools

Technical Data Sheet CA Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com