Product data sheet Characteristics

8501RSD43P14V53

Relay - miniature plug-in - 10A - 3 pole - 24VDC coil - pilot light

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 45.00 USD



Main

Main		
Range of product	8501R	7
Product or component type	Miniature Relay	
Relay type	Standard	***

Complementary

Mounting support	Socket
Switch function	3PDT
[Uc] control circuit voltage	24 V DC
Local signalling	LED green indicator when relay energised
Control type	Without test button
Rated power in HP	0.5 at 120 V AC 1 at 277 V AC
Rated breaking capacity	3 A at 120 V AC - inductive control circuit per UL 508 1.5 A at 240 V AC - inductive control circuit per UL 508 10 A at 28 V DC - resistive control circuit per UL 508 10 A at 120 V AC - resistive control circuit per UL 508 6.67 A at 277 V AC - resistive control circuit per UL 508
Maximum switching voltage	300 V at AC 30 V at DC
Contacts material	Silver alloy, gold flashed
Operating time	20 ms - pick-up 20 ms - drop-out
Shape of pin	Spade
Product compatibility	8501NR43
Height	27.3 mm
Width	30.6 mm
Depth	41.8 mm

Environment

Ambient air temperature for operation	-40131 °F
Product certifications	CSA CE UL listed UL recognized

Ordering and shipping details

Category	21143 - 8501 R	
Discount Schedule	CP2	
GTIN	00785901856108	
Nbr. of units in pkg.	25	
Package weight(Lbs)	0.13	
Returnability	N	
Country of origin	CN	

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1410 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months