## Product data sheet Characteristics

# XGHB444345

# RFID electronic tag - 13.56 MHz - flat form 40 $\times$ 40 $\times$ 15 - 3408 Bytes

Product availability: Non-Stock - Not normally stocked in distribution facility



Price\*: 158.00 USD



#### Main

Mani		
Range of product	OsiSense XG	
Product or component type	Electronic tag	
RFID electronic tag name	XGHB	
RFID frequency	13.56 MHz	
Design	Flat form 40 x 40 x 15	
Memory capacity	3.408 kB	
Station name	XGCS	
[Sn] nominal sensing distance	1.89 in (48 mm) with XGCS85 1.3 in (33 mm) with XGCS49 1.89 in (48 mm) with XGCS89	
Outer dimension	40 x 40 x 15 mm	
Quantity per set	Set of 1	
Read time	9.25 + 0.375 x (number of 16-bit words) ms	
Write time	13 + 0.8 x (number of 16-bit words) ms	
IP degree of protection	IP68	
Fixing mode	By clips By screws	

#### Complementary

Memory type	EEPROM	inter
Memory operation	Read/Write	s not
Number of read cycles	Unlimited	rtion ri
Number of write cycles	2500000 at 86 °F (30 °C) 100000 at -13158 °F (-2570 °C)	
Passing speed of object	With XGCS49 (read a serial number) With XGCS49 (read a word) With XGCS49 (read or write 10 words) With XGCS89 (read a serial number)	isclaimer: This do

With XGCS89 (read a word)
With XGCS89 (read or write 10 words)
With XGCS85 (read a serial number)
With XGCS85 (read a word)
With XGCS85 (read or write 10 words)

Data retention time	10 yr
Mounting location	Possible on metal support
Material	PBT (polybutylene terephthalate)
Product weight	0.07 lb(US) (0.031 kg)

#### Environment

Standards	ISO 14443
Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient air temperature for storage	-40185 °F (-4085 °C)
Vibration resistance	2 mm (f = 529.5 Hz) conforming to EN 60068-2-6 7 gn (f = 29.5150 Hz) conforming to EN 60068-2-6
Shock resistance	30 gn 11 ms conforming to EN 60068-2-27
IK degree of protection	IK02 conforming to EN 50102

## Ordering and shipping details

Category	22491 - SENS,IDENTIFICATION DEVICE (XGK)
Discount Schedule	DS2
GTIN	00785901601883
Nbr. of units in pkg.	1
Package weight(Lbs)	8.9999999999997E-2
Returnability	N
Country of origin	FR

## Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0824 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Available	

#### Contractual warranty

Contractadi Warranty		
Warranty period	18 months	