



Actual



Representative

**Catalog Number:** 3308  
**Product ID:** 7TAA106080R0008  
**UPC Number:** 78621003308  
**EAN Number:** 05415022257779  
**Status:** Active

Sheathed Cable Fitting, Straight, Knockout Size 2-1/2 Inch, Two Screw Connector, Malleable Iron with Zinc Plating

### Header

3D Model Available on Website

### North American Specifications (UNSPSC)

|                  |   |
|------------------|---|
| UNSPSC           | 39121419 Flex connectors  |
| IGCC             | 4573 Flex connectors  |
| Brand Name       | T&B   |
| Sub Brand        | CSA   |
| Type             | Non-Metallic Sheathed Cable Conduit Fittings  |
| Special Features | Rounded Cable Grip and Smooth Bushing Protect The Cable Sheath and Wire Insulation. Since Saddle is Threaded, Screws Do Not Travel or Extend Beyond The Connector Body As It is Clamped to The Cable. An Extra Lip on The Saddle Closes The Unused Part of The Connector Opening. |
| Application      | To Connect Non-Metallic Sheathed Cable and Flexible Cord to a Box or an Enclosure.  |
| Size             | 2-1/2 Inch  |
| Connection       | Straight  |
| Material         | Malleable Iron  |
| Finish           | Electro Zinc Plated   |
| Color            | Metallic  |
| Insulation       | No  |

### European Specifications (ETIM)

|   |  |
|---|--|
| ETIM  | EC001180 Screw connection for protective metallic hose |
| Nominal size in inch                        | 2 1/2 inch   |
| Model                                       | Straight   |
| Revolving thread                            | N  |
| Construction type                           | External thread  |
| Connection type screw connection to housing | Other  |
| Material housing                            | Other  |
| Surface protection                          | Zinc coated  |

### Packaging

|                           |                  |
|---------------------------|------------------|
| Inner Quantity            | 1                |
| Inner Dimensions (inches) | 4x4x3            |
| Outer Quantity            | 5                |
| Outer Dimensions (inches) | 16.4x5.1x5.9     |
| Weight Uom                | 152 lbs. per 100 |

### Documents / Support Tools

|                         |                      |
|-------------------------|----------------------|
| Technical Data Sheet US | Available on Website |
| Technical Data Sheet CA | Available on Website |

For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)