Catalog Number:
 GRPE-062-9-C

 Product ID:
 7TAG009750R0039

 UPC Number:
 72849410655

 EAN Number:
 05414363152033

Status: Active

Extruded Grommeting, Natural Polyethylene for Temperatures up to 85 Degrees Celsius (185 F), Height of 5.08mm (0.20 Inches), Width of 4.32mm (0.17 Inches), Thickness 1.14mm (0.045 Inches), Width Maximum Panel Thickness of 1.57mm (0.062 Inches), 30.48m (100 Foot) Reel

- Used to line panel edges and knockouts where the chafing of wires is a concern.
- Available in 8 stock sizes in 100-ft. lengths for panels from .040 .250 inches thick and in a variety of stocked materials to cover a wide range of applications.
- Application Tools: SR-100

North American Specifications (UNSPSC)	
UNSPSC	39131603 Grommet edging
IGCC	5393 Grommet edging
Brand Name	Catamount
Туре	Grommeting
Special Features	Used to line panel edges and knockouts where the
	chafing of wires is a concern
Color	Natural
Length	100 Feet/30.48m
Panel Thickness	0.045 Inches/1.14mm
Material	Polyethylene

European Specifications (ETIM)	
ETIM	EC002604 Cable bundle hose
Material	Plastic
Material quality	Polyethylene
Colour	Natural colour
Transparent	N

Packaging	
Inner Quantity	1
Inner Dimensions (inches)	15x12x1.5
Outer Quantity	15
Outer Dimensions (inches)	18.25x12.75x13.75
Weight Uom	1.09 lbs. Each

## **Documents / Support Tools**

Technical Drawing / Data Sheet US Available on Website
Technical Drawing / Data Sheet Canada Available on Website

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Actual

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com