

G81-7040

INDUSTRIAL



Models may vary from the image shown

Facts & Features

- PC/SC and EMV 2000 Compatible
- 15.9" USB Keyboard
- Top Insertion Smart Card Reader Enables Card to Stay in Plain View of the User
- Supports Maximum Smart Card Speed for Fastest Data Transmission and Highest Read & Write Performance
- Landing Contacts Ensure up to 200,000 Smart Card Insertion Cycles
- Smart Card Reader Drivers for Windows, Linux and Macintosh
- 43 Free Programmable Keys for Easy Layout Configuration

Technical Data:

Interface: USB 2.0

Current Input: max. 300 mA

Smart Card Reader

Standards:

ISO 7816, PC/SC, EMV 2000, CCID cards, CTAPI

Protocols:

T=0, T=1, I 2C (S=8), 2 wire (S=10), 3 wire (S=9)

Data transfer rate from reader to:

Card: up to 420 Kbps

PC: up to 12 Mbps



Magnetic Stripe Reader

Standards:

ISO 7811/-12, AAMVA, JIS
PCI DSS 3.0 Compliant
Others on request

Reader Head:

Up to 1 million cycles

Reading Speed:

3 – 125 inch/s at 75 Bit/inch
3 – 50 inch/s at 210 Bit/inch
Data is decoded to keyboard scancodes.

Cable Length:

Approx. 1.75 m / 5.74'

Key Layout:

Full size 104 position US key layout
Including Windows keys

Weight: (without/with packaging)

1700/2100 kg,
3.74 Lbs. / 4.4 Lbs.

Dimensions:

Approx. 405 x 220 x 64 mm (keyboard)
Approx. 15.94" x 8.6" x 2.51"
Approx. 455 x 275 x 72 mm (packaging)
Approx. 17.91" x 10.82" x 2.83"

Packaging Units:

34 keyboards per master carton
2 master cartons per pallet

Keyswitch Lifetime:

>50 million operations

Storage Temperature:

-20°C to 60°C
-4°F to 140°F

Operating Temperature:

0°C to 50°C
32°F to 120°F

Approvals:

CE, GS, VDE, cURus, FCC, C-Tick,
VCCI, BSMI (USB only) WHQL



Technical Data Contn:

Available Software:

- CHERRY Tools
MS Windows™ XP, Vista, Win 7, Win 8
- CHERRY Tools Runtime:
MS Windows™ XP, Vista, Win 7, Win 8
XP Embedded
- PC/SC Smart Card Reader Drivers
MS Windows XP, Vista, Win 7, Win 8
MS Windows™ CE 3.0 / CE.NET
(Depends on hardware) Linux, Macintosh
- OPOS Local Editions
(OLE for Point of Sale):
MS Windows™ XP, Vista, Win 7, Win 8
XP Embedded

Available Software: Continued

- OPOS Client/Server Edition
MS Windows XP, Vista, Win 7,
Win 8
XP Embedded
- JavaPOS Local Edition
(Java for Point of Sale):
MS Windows XP, XP Embedded,
Vista, Win 7, Win 8
Suse Linux V8.0/ Kernel 2.4 or
Higher
IBM JRE v1.3 andSUN JRE
V1.4.x

Delivery Volume:

Keyboard, hard copy, CDR0M

Warranty:

3 years

Order Description

<i>Product Name</i>	<i>Order Number</i>	<i>Interface</i>	<i>Color</i>
G81-7040	G81-7040LUVU-0	USB	Lt. Grey

Available in various country versions upon request.

ZF Electronic Systems Pleasant Prairie, LLC
11200 88th Avenue
Pleasant Prairie, WI 53158
USA
Phone: 262.942.6500
Internet: www.cherrycorp.com

Sales: 262.942.6562
E-Mail: CEP_sales@ZF.com
Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.