

Catalog Number: 266-I-TB

 Product ID:
 7TAA106070R0015

 UPC Number:
 78620989548

 EAN Number:
 05414363450016

Status: Active

Squeeze Connector, 90 Degree Bend, Trade Size 3/8 Inch, Knockout Size 1/2 Inch, Cable Range 0.406 to 0.656 Inch, Insulated Throat, Steel

North American Specifications (UNSPSC)		
UNSPSC	39121419 Flex connectors	
IGCC	4573 Flex connectors	
Brand Name	T&B	
Туре	Armored Cable/Flexible Metal Conduit Fittings	
Special Features	Cap Lifts off by Simply Loosening Screws Part	
	Way, Only Two Screws to Tighten	
Application	For Use with Armored Cable and Flexible Metal	
	Conduit	
Standard	UL E23018, CSA 2884	
Size	3/8 Inch	
Connection	90 Degree	
Conductor Range	0.406 to 0.656 Inch	
Material	Steel	
Finish	Zinc Plated	
Color	Metallic	
Insulation	Insulated Throat	

European Specifications (ETIM)	
ETIM	EC001180 Screw connection for protective metallic
	hose
Nominal size in inch	3/8 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to	Other
housing	
Material housing	Steel
Thread length	36.51mm
Approved in combination with protective	Υ
conduit CSA	
Approved in combination with protective conduit UL	Υ

Packaging	
Inner Quantity	50
Inner Dimensions (inches)	8.25x5.25x4.25
Outer Quantity	100
Outer Dimensions (inches)	8.68x5.43x8.37
Weight Uom	11.5 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet WSD-000409

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321



Email:techsupport@tnb.com