

Product data sheet

Characteristics

XZCPA0566L5

pre-wired connectors XZ - straight female - M8 - 3 pins - cable PUR 5m

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 34.40 USD



Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	Application

Complementary

Electrical connection	M8, 3 pins straight female connector
Cable connector fixing	Screw-on
Collar material	Stainless steel 316L
Status LED	Without
Cable length	16.4 ft (5 m)
Cable outer diameter	0.2 in (5 mm)
Cable composition	3 x 0.34 mm ²
Wire insulation material	PUR
System Voltage	75 V DC
Line Rated Current	4 A
Contact resistance	5000 μOhm
Insulating resistance	1 GΩ
Product weight	0.39 lb(US) (0.175 kg)

Environment


IP degree of protection	IP68
Ambient air temperature for operation	-13...185 °F (-25...85 °C) (static)
Ambient air temperature for storage	-31...212 °F (-35...100 °C)

Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	003389119021579
Nbr. of units in pkg.	1

Package weight(Lbs)	0.40000000000000002
Returnability	N
Country of origin	PL

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0601 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
------------------------	---

Contractual warranty

Warranty period	18 months
-----------------	-----------
