



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₁	REVISED	K.LE 4-18-97	<i>[Signature]</i> 6/21/97
B	PER EC 0U20-0116-01-03	16NOV01	<i>C. Hoang</i> 16NOV01

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35
COUPLING NUT SLIDE ASS'Y	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303 PER ASTM-D-1457	ELECTRO-POLISH
CONTACT EXT.	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CENTER CONTACT	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204
COMPONENT	MATERIAL	FINISH

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY	DATE	AMP	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	SWA	9-11-84		
	CHECKED BY	DAC 9-12-84		
FRAC. ± 1/64	DEC. ± .005	ANGLES ± 1°	APPD BY	ACS 9-13-84
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE 7mm PRECISION TO "OSN" JACK ADAPTER		
	NO. A.P. N/A	SIZE B	CODE IDENT NO. 26805	7482-5004-00
		SCALE 3:1		REV 01 ₁
				SHEET 1 OF 1

NOTES:
 IMPEDANCE: 50 OHMS
 FREQUENCY RANGE: 0-18 GHz
 MAX VSWR: 1.015 + .002f (GHz)
 RF LEAKAGE: 122 dB @ 4 GHz

.XXX = in
 XX.X = mm (REF)

CUSTOMER DRAWING

AMP PART # 1062026-1
 SHEET 1 OF 1 REV B