

# C48 UK Wall Mount 16-20VA Transformer Series

## Features

- 230 VAC Input
- UK Wall Plug Style
- Rated for Continuous Duty
- AC outputs up to 20VA
- Meets Safety Agency Requirements
- Complies with EMI/RFI Regulations
- CE Compliant
- Impact Resistant Polycarbonate Enclosure
- Private Label Marking Available
- 1 Year Warranty
- Modified and Custom Designs Also Available
- Manufactured in China

Ault Model	Rated Output Volts AC	Maximum Current-Amps	Maximum VA
C48-062667-A000G	6	2.67	16.0
C48-072286-A000G	7	2.29	16.0
C48-082000-A000G	8	2.00	16.0
C48-091778-A000G	9	1.78	16.0
C48-101600-A000G	10	1.60	16.0
C48-111455-A000G	11	1.46	16.0
C48-121667-A000G	12	1.67	20.0
C48-141333-A000G	14	1.14	16.0
C48-151333-A000G	15	1.33	20.0
C48-161000-A000G	16	1.00	16.0
C48-180889-A000G	18	0.89	16.0
C48-200750-A000G	20	0.75	15.0
C48-220727-A000G	22	0.73	16.0
C48-240833-A000G	24	0.83	20.0

\*To be assigned at time of order placement

### Input

- Voltage 230 VAC
- Line Frequency 50 Hz
- Connector UK Wall Plug, No Ground

### Electrical

- Topology Step Down AC/AC Transformer
- Dielectric Withstand 3000 VAC primary-secondary  
1500 VAC primary-core  
500 VAC secondary-core
- Protection Current, Thermal or Energy Limiting
- EMI Complies with EMC Directives
- CE CE Compliant

### Safety Approvals

- Safety Agencies TUV EN60950

### Environmental

- Operating Temperature 0° to 40° C with no derating
- Storage Temperature -30° to +85° C
- Relative Humidity 5% to 95% non-condensing
- Altitude 0-10,000 feet
- Cooling Convectional - non vented case

### Mechanical

- Case Dimensions C48 - UK Wall Plug  
3.2 L x 2.2 W x 1.9H (in)  
81 L x 55 W x 48 H (mm)
- Case Material Black 94 V1 Polycarbonate
- Weight 18 ounces, 520 grams, (excluding cord)
- Cord and Connector 6 ft., 2 Conductor, 22-24 AWG  
Ault #3 Connector  
Other Connectors Available

## ONE YEAR WARRANTY

