# Thomas&Betts



Actual

Catalog Number: Product ID: UPC Number: EAN Number: Status: **GRPE-187-9-C** 7TAG009750R0043 72849407140 05414363023777 Active

Extruded Grommeting, Natural Polyethylene for Temperatures up to 85 Degrees Celsius (185 F), Height of 6.85mm (0.27 Inches), Width of 6.98mm (0.275 Inches), Thickness 1.27mm (0.05 Inches), Width Maximum Panel Thickness of 4.74mm (0.187 Inches), 30.48m (100 Foot) Reel

- Used to line panel edges and knockouts where the chafing of wires is a concern.
- Available in 8 stock sizes in 100-ft. lengths for panels from .040 .250 inches thick and in a variety of stocked materials to cover a wide range of applications.
- Application Tools: SR-100

North American Specifications (UNSPSC)	
UNSPSC	39131603 Grommet edging
IGCC	5393 Grommet edging
Brand Name	Catamount
Туре	Grommeting
Special Features	Used to line panel edges and knockouts where the
	chafing of wires is a concern.
Color	Natural
Panel Thickness	0.187
Material	Polyethylene

## **European Specifications (ETIM)**

ETIM	EC002604 Cable bundle hose
Material	Plastic
Material quality	Polyethylene
Colour	Natural colour
Transparent	Ν

# Packaging

Fackaging	
Inner Quantity	1
Inner Dimensions (inches)	20x13x2
Outer Quantity	10
Outer Dimensions (inches)	18x12.5x12
Weight Uom	1.22 lbs. Each

### **Documents / Support Tools**

Technical Drawing / Data Sheet Canada Available on Website

#### For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com