

# Product data sheet


## Characteristics

# XZCE13M125M

adaptor, metal - tapped hole Pg 13.5 - for male connector, M12, 5-wire

Product availability : Non-Stock - Not normally stocked in distribution facility

Price\* : 25.50 USD



### Main

Accessory / separate part designation	5-wire connector adaptor
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector adaptor
Cable composition	4 x 0.34 mm <sup>2</sup> + 1 x 0.5 mm <sup>2</sup>
Thread type	Pg 13.5
Line Rated Current	4 A

### Complementary

Cable length	3.94 in (100 mm)
Total number of wires	5
Electrical connection	1 male connector M12 5 straight
Cable connector fixing	Screw-on
Body material	Metal
Insulation resistance	> 1000000000 Ohm
Resistance across terminals	<= 5000 mOhm
System Voltage	250 V AC 300 V DC
Product weight	0.06 lb(US) (0.025 kg)

### Environment

IP degree of protection	IP67
Ambient air temperature for operation	-13...176 °F (-25...80 °C)

### Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	003389110835519
Nbr. of units in pkg.	1
Package weight(Lbs)	5.000000000000003E-2

---

Returnability	N
Country of origin	CZ

---

### Offer Sustainability

---

RoHS (date code: YYWW)	Compliant - since 0545 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
------------------------	---

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---