

Representative

Catalog Number: 3120

 Product ID:
 7TAA106030R0007

 UPC Number:
 78621003120

 EAN Number:
 05414363140825

Status: Active

Metal-Clad and Armored Cable Fitting, Straight, Trade Size 2 Inch, Knockout Size 2 Inch, Cable Range 2.312 to 2.500 Inch, Malleable Iron with Zinc Plating, Nylon Insulated

- The tough lining of insulation and the Tite-Bite principles make these connectors a must when conductors are subject to conditions of vibration or strain.
- To connect and effectively bond armored cable or flexible metal conduit to a box or an enclosure.

North American Specifications (UNSPSC)		
UNSPSC	39121419 Flex connectors	
IGCC	4573 Flex connectors	
Brand Name	T&B	
Туре	Armored Cable/Flexible Metal Conduit Fittings	
Special Features	Unique Saddle Design Firmly Secures Cable In	
	Place, Provides Holding Power In Excess of List-	
	ing Agency Requirements and Assures High Quality	
	Bonding	
Application	For Use with Armored Cable and Flexible Metal	
	Conduit.	
Standard	UL E23018, CSA 2884	
Size	2 Inch	
Connection	Straight	
Conductor Range	2.312 to 2.500 Inch	
Material	Malleable Iron	
Finish	Electro Zinc Plated	
Color	Metallic	
Insulation	Nylon	

<b>European Specifications (ETIM</b>	ean Specifications (ETIM)	
ETIM	EC001180 Screw connection for protective metallic	
	hose	
Nominal size in inch	2 inch	
Model	Straight	
Revolving thread	N	
Construction type	External thread	
Connection type screw connection to	Other	
housing		
Material housing	Other	
Surface protection	Zinc coated	
Total length	49.21mm	

Packaging	
Inner Quantity	1
Inner Dimensions (inches)	4.5x5x3
Outer Quantity	5
Outer Dimensions (inches)	21.6x5.4x7
Weight Uom	159 lbs. per 100

<b>Documents / Support Tools</b>	
Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website



For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com