

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0845070012](#)
Status: **Active**
Overview: XRC (Extra Rugged Circular) Sealed Plugs and Receptacles
Description: XRC Sealed Plug with Socket Insert, Shell Size 18, 14 Circuits, Blue Ring

Documents:

3D Model	Application Specification AS-84501-001-004 (PDF)
Drawing (PDF)	Packaging Specification PK-84501-001-001 (PDF)
Product Specification PS-84501-001-001 (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification

UL E152602

General

Product Family	Crimp Housings
Series	84507
Application	Power, Wire-to-Wire
Comments	IP67 rated; conforms to UL 1977. NOT suitable for automotive applications with requirements such as USCAR-2, USCAR-25, GMW3191, AK Testing, J2030, Volvo Technology Requirements, and Toyota Connector Spec (TCS)
More Detailed Tech Information Overview	Extra thin wall wire seals XRC (Extra Rugged Circular) Sealed Plugs and Receptacles
Product Name	XRC
UPC	822350758543

Physical

Circuits (maximum)	14
Flammability	94V-0
Gender	Plug
Glow-Wire Capable	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Net Weight	12.590/g
Number of Rows	0
Packaging Type	Tray
Panel Mount	Yes
Pitch - Mating Interface	N/A
Pitch - Termination Interface	N/A
Polarized to Mating Part	Yes
Ports	1
Stackable	No
Temperature Range - Operating	-55°C to +125°C

Material Info

Reference - Drawing Numbers

Application Specification	AS-84501-001-004
Packaging Specification	PK-84501-001-001
Product Specification	PS-84501-001-001
Sales Drawing	SD-84507-002-001



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -ED/01/2018 (15 January 2018)

Halogen-Free

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series

[84507 Series](#)

Mates With

[84502 Receptacle](#)

Use With

[84525 XRC Sealed Terminal Socket](#)