



Actual



Representative

Catalog Number: 2920NM
Product ID: 7TAD105200R0000
UPC Number: 78621079740
EAN Number: 05414363101710
Status: Active

Liquidtight Strain Relief Connector, Straight, 1/2 Inch NPT Thread, Cable Range 0.125 Inch/3.2mm to 0.375 Inch/9.5mm, Throat Diameter 0.55 Inch, IP65 Rating, UV Resistant Polyamide 6.6 Body, Black

- Extended range with superior strain relief.
- Reduced overall size, fits into tighter spaces.
- Gland nut designed to restrict cable bending.
- Provide a means for passing a cord cable into an enclosure through a bulkhead
- Suitable for Ordinary, Wet or Dry locations.

North American Specifications (UNSPSC)

| | |
|--------------------------|--|
| UNSPSC | 39121431 Cable gland connector |
| IGCC | 4601 Cable gland connector |
| Brand Name | T&B |
| Type | Cord Connectors-Straight |
| Special Features | Extended Range with Superior Strain Relief |
| Application | A Liquidtight Fitting to Secure Flexible Cord or Power Cable to a Box or Enclosure and Provide Strain Relief |
| Standard | UL E13938, CSA 52391 |
| Size | 1/2 Inch |
| Conductor Range | 0.125 Inch/3.2mm to 0.375 Inch/9.5mm |
| Material | Polyamide/Nylon 6.6 |
| Color | Black |
| Temperature Rating | -34 to +105 Degrees C |
| Environmental Conditions | Ordinary, Wet, or Dry Locations |

European Specifications (ETIM)

| | |
|--|----------------------------|
| ETIM | EC000441 Cable screw gland |
| Thread type | NPT |
| Nominal thread size inch/gas pipe thread | 1/2 inch |
| Thread length | 15.875mm |
| Suitable for cable diameter | 3.2-9.5mm |
| Material | Plastic |
| Material quality | Polyamide (PA) |
| Degree of protection (IP) | IP65 |
| Colour | Black |
| Model | Straight |
| Strain relief | Y |
| Operating temperature | -34-+105°C |

Packaging

| | |
|---------------------------|----------------|
| Inner Quantity | 25 |
| Inner Dimensions (inches) | 6x5x4 |
| Outer Quantity | 100 |
| Outer Dimensions (inches) | 12.75x8.75x5.5 |
| Weight Uom | 5 lbs. per 100 |

Documents / Support Tools

| | |
|-----------------------------------|----------------------|
| Technical Drawing / Data Sheet US | Available on Website |
|-----------------------------------|----------------------|

Technical Drawing / Data Sheet Canada Available on Website
Instruction Sheet TA00927-TB2

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com