

# Product data sheet

## Characteristics

# XZCPV1564L5

pre-wired connectors XZ - straight male - M12 - 5 pins - cable PVC 5m

Product availability : Non-Stock - Not normally stocked in distribution facility

Price\* : 28.00 USD



### Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

### Complementary

Electrical connection	M12, 5 pins straight male connector
Cable connector fixing	Screw-on
Collar material	Metal
Status LED	Without
Cable length	16.4 ft (5 m)
Cable outer diameter	0.2 in (5.2 mm)
Cable composition	5 x 0.25 mm <sup>2</sup>
Wire insulation material	PVC
System Voltage	250 V AC 300 V DC
Line Rated Current	3 A
Contact resistance	5000 μOhm
Insulating resistance	1 GΩ
Product weight	0.4 lb(US) (0.18 kg)

### Environment


IP degree of protection	IP65 IP67
Product certifications	CULus
Ambient air temperature for operation	-13...176 °F (-25...80 °C) (static)
Ambient air temperature for storage	-13...176 °F (-25...80 °C)

### Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3

GTIN	00785901951704
Nbr. of units in pkg.	1
Package weight(Lbs)	0.47000000000000003
Returnability	N
Country of origin	PL

**Offer Sustainability**

RoHS (date code: YYWW)	Compliant - since 1201 - Schneider Electric declaration of conformity <a href="#"> Schneider Electric declaration of conformity</a>
------------------------	---

**Contractual warranty**

Warranty period	18 months
-----------------	-----------