



Representative

Catalog Number: 54895L
Product ID: 7TAA014120R0016
UPC Number: 78621017965
EAN Number: 05415022348231
Status: Active

E-Z-Ground Figure 6-6 Copper Compression Ground Grid Connector for Cable Range 250 kcmil - 500 kcmil, Ground Rod 5/8 - 3/4

- E-Z-Ground® connectors are designed for direct burial and offer a safe, efficient alternative to exothermic welding products.
- Application Tools: TBM14M, 13100A, TBM15I

North American Specifications (UNSPSC)

UNSPSC	39121613 Grounding devices or assemblies
IGCC	4909 Grounding devices or assemblies
Brand Name	Color-Keyed
Type	E-Z-Ground Compression Grounding
Special Features	E-Z-Ground® connectors are designed for direct burial and offer a safe, efficient alternative to exothermic welding products.
Standard	CSA, UL, IEEE
Conductor Size	250 kcmil - 500 kcmil, Ground Rod 5/8 - 3/4

Packaging

Inner Dimensions (inches)	xx
Outer Quantity	25
Outer Dimensions (inches)	11.12x13.12x13.75
Weight Uom	1 lbs. Each

Documents / Support Tools

SDS US 1	SDS-00045-TB2
Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website
Instruction Sheet 1	TA02146-TB2

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com