



Actual



Representative

**Catalog Number:** 2449  
**Product ID:** 7TBD105140R0018  
**UPC Number:** 78621002449  
**Status:** Active

Watertight Connector for Oval Cable, Hub Size 2 Inch, Die Cast Zinc Body with Neoprene Bushing, Oval Cable Range Maximum 1.062 X 1.765 Inch, Minimum .850 X 1.550 Inch

- The tapered neoprene bushings are resistant to oil, sunlight and water. Hex gland and body take the same wrench opening and a stainless steel slip ring prevents cable from twisting as gland ring is being tightened. Threads on the body are tapered for water

### Header

3D Model Available on Website

### North American Specifications (UNSPSC)

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	T&B
Type	Watertight Connectors for Oval Cable
Special Features	A Design with Two Tapers Inside the Body-A Slow One and a Fast One-Permits the Stocking of Fewer Connectors for Varied Cable Sizes and Allows Maximum Take-Up.
Application	To Connect Underground Feeder Cables to a Box or an Enclosure
Standard	UL E15170, CSA 4484
Size	2 Inches
Conductor Range	.850x1.550 to 1.062x1.765 Inch
Material	Zinc Die Cast
Color	Metallic

### European Specifications (ETIM)

ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	2 inch
Material	Metal
Material quality	Other
Colour	Natural colour
Model	Straight

### Packaging

Inner Quantity	5
Inner Dimensions (inches)	8x5x4
Outer Quantity	10
Outer Dimensions (inches)	10.8x8.39x4.5
Weight Uom	100 lbs. per 100

### Documents / Support Tools

Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com