

Catalog Number: CPO1000-2-B
Product ID: 7TAA017310R0015
UPC Number: 78621083276
Status: Active



Thin-Wall Heat-Shrinkable Tubing for Cable Range 2/0 - 350 MCM, Expanded Diameter 1, Length 300 feet reel, rated for 600 Volt, 125 degrees C, Material: Cross-linked polyolefin - Non-lined, Red

- Flame-retardant, cross-linked polyolefin.
- Meets UL 224, 125°C; CSA 22.2 No. 198.1, 125°C; MIL-DTL-23053/5 Class 1&2; AMS 3636 & 3637; DEF STAN 59-97, Issue 3, Type 2a

Actual

North American Specifications (UNSPSC)

| | |
|------------------|-------------------------------------------|
| UNSPSC | 39121723 Heat shrinkable tube |
| IGCC | 5073 Heat shrinkable tube |
| Brand Name | Shrink-Kon |
| Type | Thin-Wall Heat-Shrinkable Tubing |
| Special Features | Flame-retardant, cross-linked polyolefin. |
| Shrink Ratio | 2:1 |
| Thickness | Thin |
| Length | 300 |
| Color | Red |

European Specifications (ETIM)

| | |
|-----------------------------------|------------------------|
| ETIM | EC000217 Shrink tubing |
| Type | Heat-shrink |
| Model | Thin-walled |
| Shrink rate | 2:1 |
| Inner diameter before heat-shrink | 25.4mm |
| Inner diameter after heat-shrink | 12.7mm |
| Nominal diameter inch | 1 inch |
| Wall thickness after shrinking | 10.16mm |
| Length | 91.44m |
| Operation temperature | -55-+135°C |
| Colour | Red |
| Material | Polyolefin (PO-X) |
| Halogen free | N |
| With inner glue | N |
| Printable | N |
| UL approval | Y |

Packaging

| | |
|---------------------------|-------------------|
| Outer Quantity | 1 |
| Outer Dimensions (inches) | 20.1x9x20.5 |
| Weight Uom | 1300 lbs. per 100 |

Documents / Support Tools

| | |
|---------------------------------------|----------------------|
| Technical Drawing / Data Sheet US | Available on Website |
| Technical Drawing / Data Sheet Canada | Available on Website |
| Safety Data Sheet (SDS) US | SDS-00046-TB2 |

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com