Product data sheet Characteristics

XZCP0766L10

pre-wired connectors XZ - elbowed female - M8 - 3 pins - cable PUR 10m

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 45.40 USD



Main

TVI CALL		2
Accessory / separate part category	Cabling accessory	_
Accessory / separate part type	Pre-wired connectors	_ 000
Series name	General purpose	-40

Complementary

Electrical connection	M8, 3 pins elbowed female connector	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	2 PNP LEDs	
Cable length	32.81 ft (10 m)	
Cable outer diameter	0.2 in (5.2 mm)	
Cable composition	3 x 0.34 mm ²	
Wire insulation material	PUR	
System Voltage	1030 V DC	
Line Rated Current	4 A	
Contact resistance	5000 μOhm	
Insulating resistance	1 GΩ	
Product weight	0.5 lb(US) (0.225 kg)	

Environment

Environment		. <u>u</u>
IP degree of protection	IP65 IP67 IP69K	constant
Product certifications	CULus	
Ambient air temperature for operation	-40176 °F (-4080 °C) (static) 23176 °F (-580 °C) (flexing)	rie T

Ambient air temperature for storage	-40176 °F (-4080 °C)
Ordering and shipping details	
Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	003389110762853
Nbr. of units in pkg.	1
Package weight(Lbs)	0.5300000000000003
Returnability	N
Country of origin	CZ

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0649 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Available	

Contractual warranty

Contractad Warranty		
Warranty period	18 months	