Product data sheet Characteristics

XZCC20FCM30B

female, 1/2 20UNF, 3-pin, elbowed connector cable gland Pg 7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price* : 20.00 USD



Accessory / separate part category	Cabling accessories	
Accessory / separate part type	Connector	
Electrical connection	Elbowed female connector 1/2 20 UNF, 3 pins	
Collar material	Metal	
Status LED	Without	-
Cable connection	Screw terminal / wire size <= 0.75 mm² / clamping capacity 0.120.24 in (36 mm)	

Complementary

Cable gland type	Pg 7	
Cable connector fixing	Screw-on	
System Voltage	250 V AC	
Line Rated Current	4 A	
Enclosure material	Plastic	
Insulating resistance	> 1000 GΩ	
Contact resistance	<= 8000 μOhm	
Product weight	0.04 lb(US) (0.02 kg)	

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-40185 °F (-4085 °C)

Ordering and shipping details

Main		
Accessory / separate part category	Cabling accessories	
Accessory / separate part type	Connector	
Electrical connection	Elbowed female connector 1/2 20 UNF, 3 pins	
Collar material	Metal	
Status LED	Without	
Cable connection	Screw terminal / wire size <= 0.75 mm² / clamping capacity 0.120.24 in (36 mm)	
Complementary		
Cable gland type	Pg 7	
Cable connector fixing	Screw-on	
System Voltage	250 V AC	
Line Rated Current	4 A	
Enclosure material	Plastic	
Insulating resistance	> 1000 GΩ	
Contact resistance	<= 8000 μOhm	
Product weight	0.04 lb(US) (0.02 kg)	
Environment		
IP degree of protection	IP67	
Ambient air temperature for operation	-40185 °F (-4085 °C)	
Ordering and shipping details		
Category	22483 - MACHINE CABLES	
Discount Schedule	DS3	
GTIN	00785901400493	
Nbr. of units in pkg.	1	
Package weight(Lbs)	5.999999999998E-2	
Returnability	N	
Country of origin	CZ	
him 24, 2040		

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0545 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
Contractual warranty	
Confractual Warranty	