

# AULT SPECIFICATIONS

## 12-20VA Wall Plug Series

### INPUT

**Voltage** 230 VAC  
**Line Frequency** 50 Hz  
**Configuration** Euro Wall Plug, No Ground

### OUTPUT

<i>Model Number</i>	<i>Rated Output Volts AC</i>	<i>Output Current Amps</i>	<i>Max VA</i>	<i>Agency Approvals</i>
A48-062667-A000G	6	2.67	16.0	EN60950
A48-072286-A000G	7	2.29	16.0	EN60950
A48-082000-A000G	8	2.00	16.0	EN60950
A48-091778-A000G	9	1.78	16.0	EN60950
A48-101600-A000G	10	1.60	16.0	EN60950
A48-111455-A000G	11	1.46	16.0	EN60950
A48-141143-A000G	14	1.14	16.0	EN60950
A48-151333-A000G	15	1.33	20.0	EN60950
A48-161000-A000G	16	1.00	16.0	EN60950
A48-180889-A000G	18	0.89	16.0	EN60950
A48-200750-A000G	20	0.75	15.0	EN60742
A48-220727 A000G	22	0.73	16.0	EN60950
A48-240833-A000G	24	0.83	20.0	EN60742

\*To be assigned at time of order placement.

### ELECTRICAL

**Topology** Step Down AC/AC Transformer  
**Dielectric Withstand** 3000 VAC primary-secondary  
**Protection** Current, Thermal or Energy Limiting  
**EMI** Complies with EMC Directives  
**CE** CE Compliant

### ENVIRONMENTAL

**Operating Temperature** 0° to 40° C with no derating  
**Storage Temperature** -30° to +85° C  
**Relative Humidity** 5% to 95% non-condensing  
**Altitude** 0 - 10,000 feet  
**Cooling** Convectional-non vented case

### MECHANICAL

**Case and Dimensions** A48 - Euro Wall Plug  
81 L X 55 W X 48 H (mm)  
3.2 L X 2.2 W X 1.9 H (in)  
**Case Material** Black 94V1 Polycarbonate  
**Weight** 18 ounces, 520 grams, (excluding cord)  
**Cord and Connectors** 6 ft., 2 Conductor, 22-24 AWG, Ault #3 Connector  
Other connectors are also available.

### WARRANTY

1 Year