

Actual



Representative

Catalog Number: 2940AL

 Product ID:
 7TBD105110R0005

 UPC Number:
 78621079719

 EAN Number:
 05414363140382

Status: Active

Liquidtight Strain Relief Connector, 1 Inch, Straight, Cord Range 0.310 to 0.560 Inch, Throat Diameter 9/16 Inch, Aluminum Body, Glandnut, and Grip, Rubber Bushing

- Extended range with superior strain relief.
- Reduced overall size, fits into tighter spaces.
- Gland nut designed to restrict cable bending.
- Provide a means for passing a cord cable into an enclosure through a bulkhead
- Suitable for Ordinary, Wet or Dry locations.
- Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

North American Specifications (UNSPSC)		
UNSPSC	39121431 Cable gland connector	
IGCC	4601 Cable gland connector	
Brand Name	T&B	
Туре	Cord Connectors-Straight	
Special Features	Extended Range with Superior Strain Relief	
Application	Provide a Means for Passing a Cord Cable Into an	
	Enclosure Through a Bulkhead	
Standard	UL E13938, CSA 52391	
Size	1 Inch	
Conductor Range	0.310 to 0.560 Inch	
Material	Aluminum	
Color	Metallic	
Environmental Conditions	Ordinary, Wet, or Dry Locations	

European Specifications (ETIM)		
ETIM	EC000441 Cable screw gland	
Thread type	NPT	
Nominal thread size inch/gas pipe thread	1 inch	
Thread length	26.98mm	
Suitable for cable diameter	7.874-14.224mm	
Material	Metal	
Material quality	Aluminium	
Colour	Natural colour	
Model	Straight	
Strain relief	Υ	

Packaging	
Inner Quantity	10
Inner Dimensions (inches)	6x4.5x3
Outer Quantity	100
Outer Dimensions (inches)	24.1x13x3.9
Weight Uom	15.5 lbs. per 100

Documents / Support Tools	
Technical Drawing / Data Sheet	WSD-000077
Technical Drawing / Data Sheet Canada	Available on Website



For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com