

Actual

Catalog Number: 269

 Product ID:
 7TAA106060R0006

 UPC Number:
 78621000269

Status: Active

Squeeze Connector, 45 Degree Bend, Trade Size 3/4 Inch, Knockout Size 3/4 Inch, Cable Range 1.000 to 1.125 Inch, Steel

North American Specifications (UNSPSC)		
UNSPSC	39121419 Flex connectors	
IGCC	4573 Flex connectors	
Brand Name	T&B	
Туре	Armored Cable/Flexible Metal Conduit Fittings	
Special Features	Fast and Easy Installation, Simply Loosen Screws	
	Partway to Lift off Cap	
Application	For Use with Armored Cable and Flexible Metal	
	Conduit	
Standard	UL E23018, CSA 2884	
Size	3/4 Inch	
Connection	45 Degree	
Conductor Range	1.000 to 1.125 Inch	
Material	Malleable Iron	
Finish	Zinc Plated	
Color	Metallic	
Insulation	No	

European Specifications (ETIM)		
ETIM	EC001180 Screw connection for protective metallic	
	hose	
Nominal size in inch	3/4 inch	
Model	45°-elbow	
Revolving thread	N	
Construction type	External thread	
Connection type screw connection to	Other	
housing		
Material housing	Steel	
Thread length	39.68mm	
Approved in combination with protective	Υ	
conduit CSA		
Approved in combination with protective conduit UL	Υ	

Packaging	
Inner Quantity	25
Inner Dimensions (inches)	10.4x7.2x4.5
Outer Quantity	50
Outer Dimensions (inches)	12.3x11.8x9.3
Weight Uom	25 lbs. per 100

Documents / Support Tools		
Technical Data Sheet US	Available on Website	
Technical Data Sheet CA	Available on Website	

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321



Email:techsupport@tnb.com